



**University of
Zurich**^{UZH}

**Zurich Open Repository and
Archive**

University of Zurich
University Library
Strickhofstrasse 39
CH-8057 Zurich
www.zora.uzh.ch

Year: 2021

Exploring Intuitive Lifelog Retrieval and Interaction Modes in Virtual Reality with vitrivr-VR

Spiess, Florian ; Gasser, Ralph ; Heller, Silvan ; Rossetto, Luca ; Sauter, Loris ; van Zanten, Milan ; Schuldt, Heiko

DOI: <https://doi.org/10.1145/3463948.3469061>

Posted at the Zurich Open Repository and Archive, University of Zurich

ZORA URL: <https://doi.org/10.5167/uzh-206328>

Conference or Workshop Item

Published Version

Originally published at:

Spiess, Florian; Gasser, Ralph; Heller, Silvan; Rossetto, Luca; Sauter, Loris; van Zanten, Milan; Schuldt, Heiko (2021). Exploring Intuitive Lifelog Retrieval and Interaction Modes in Virtual Reality with vitrivr-VR. In: ICMR '21: International Conference on Multimedia Retrieval, Taipei Taiwan, 21 September 2021. ACM, 17-22.

DOI: <https://doi.org/10.1145/3463948.3469061>

Exploring Intuitive Lifelog Retrieval and Interaction Modes in Virtual Reality with vitrivr-VR

Florian Spiess
University of Basel
Basel, Switzerland
florian.spiess@unibas.ch

Ralph Gasser
University of Basel
Basel, Switzerland
ralph.gasser@unibas.ch

Silvan Heller
University of Basel
Basel, Switzerland
silvan.heller@unibas.ch

Luca Rossetto
University of Zurich
Zurich, Switzerland
rossetto@ifi.uzh.ch

Loris Sauter
University of Basel
Basel, Switzerland
loris.sauter@unibas.ch

Milan van Zanten
University of Basel
Basel, Switzerland
milan.vanzanten@unibas.ch

Heiko Schuldt
University of Basel
Basel, Switzerland
heiko.schuldt@unibas.ch

ABSTRACT

The multimodal nature of lifelog data collections poses unique challenges for multimedia management and retrieval systems. The Lifelog Search Challenge (LSC) offers an annual evaluation platform for such interactive retrieval systems. They compete against one another in finding items of interest within a set time frame.

In this paper, we present the multimedia retrieval system vitrivr-VR, the latest addition to the vitrivr stack, which participated in the LSC in recent years. vitrivr-VR leverages the 3D space in virtual reality (VR) to offer novel retrieval and user interaction models, which we describe with a special focus on design decisions taken for the participation in the LSC.

CCS CONCEPTS

• **Information systems** → **Image search; Search interfaces; Query representation**; • **Human-centered computing** → **Virtual reality**.

KEYWORDS

Lifelog Search Challenge, Virtual Reality, Interactive Lifelog Retrieval

ACM Reference Format:

Florian Spiess, Ralph Gasser, Silvan Heller, Luca Rossetto, Loris Sauter, Milan van Zanten, and Heiko Schuldt. 2021. Exploring Intuitive Lifelog Retrieval and Interaction Modes in Virtual Reality with vitrivr-VR. In *Proceedings of the 4th Annual Lifelog Search Challenge (LSC '21)*, August 21, 2021, Taipei, Taiwan. ACM, New York, NY, USA, 6 pages. <https://doi.org/10.1145/3463948.3469061>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

LSC '21, August 21, 2021, Taipei, Taiwan

© 2021 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-1-4503-8533-6/21/08...\$15.00

<https://doi.org/10.1145/3463948.3469061>

1 INTRODUCTION

A lifelog is a record of different aspects of one's personal activities throughout the day at varying levels of detail. With smartphones and wearable devices becoming more prolific, the act of lifelogging has become more accessible to a growing audience and the information that can be gathered is expanding both in terms of volume and variety. The data typically found in a lifelog can be anything from highly structured information, such as metrics about one's physical condition (e.g., blood pressure, pulse) or metadata about one's location (e.g., coordinates, speed), to highly unstructured information, such as images or video sequences of random encounters during the day. Some lifeloggers even use wearable cameras that take pictures at regular intervals to create an extensive log of their daily routine.

There are many different motivations to keep a lifelog, ranging from a hobby of technology enthusiasts to concrete applications in personal healthcare and medicine to keeping a record of certain activities in professional life. Irrespective of the motivation, lifelogging poses very interesting research questions in regards to the storage, management, and search in such multi-modal data collections, especially given the huge amounts of information one can accumulate over a lifetime. It is therefore not surprising that a dedicated field of research has emerged around the subject of *lifelogging* [10] and retrieval in lifelog data collections [9].

The *Lifelog Search Challenge (LSC)* [11] is an annual event co-located with the *International Conference on Multimedia Retrieval (ICMR)*. The LSC offers a platform for testing and comparing information retrieval systems on lifelog data. The competitive setting involves solving a selection of retrieval tasks within a set time limit. The 2021 installment of the LSC [11] operates on the same dataset used during the LSC 2020 [9]. It covers 115 individual days between February 23, 2015 and May 05, 2018. The data contains a total of 193'911 images from two different perspectives in a 1024px × 768px resolution as well as the associated metadata such as local time, geo references, sensor readings, and other information.

In this paper we present vitivr-VR, a first-time participant in the LSC. This newest addition to the vitivr stack [26], which has participated in the LSC several times already, offers a novel user interaction and retrieval model that leverages the 3D space offered by virtual reality (VR). This paper provides an overview of the vitivr-VR system participating in the LSC 2021, with a focus on the aspects and design decisions most relevant for the LSC.

The remainder of this paper is structured as follows: Section 2 briefly surveys related work. Section 3 gives an overview of vitivr-VR’s system architecture and describes the retrieval modalities and the novel user interaction model employed, and Section 4 concludes and offers an outlook.

2 RELATED WORK

Lifelogging as a dedicated area of research has already been proposed and described in 2014 [10] with a focus on its information retrieval aspects. The Lifelog Search Challenge (LSC) 2021 [11] is the fourth installment of the LSC and offers an annual platform for interactive lifelog retrieval systems to compare and compete. vitivr is taking part for the third time [14], with previous participation in 2019 and 2020. In both previous cases, a conventional, web-based user interface [8] has been used. The main contribution in 2019 was extending vitivr to support pure Boolean retrieval queries, which are a requirement for the LSC [20], whereas in 2020, we added support for temporal scoring, staged querying and deep learning based concept detection [12]. One of the main takeaways of these two iterations is that an effective user interface for result exploration is at least as important as an expressive retrieval model. This is also a lesson learned from analyses of the Video Browser Showdown (VBS) [18, 22], where vitivr is an active participant [13, 27, 28]. vitivr has experimented with exploratory user interfaces in the past [15].

The idea of using VR as a means of user interaction in lifelog retrieval is not new. In fact, the very first winner of the LSC [4] – the Virtual Reality Lifelog Explorer (VRLE) – featured a VR UI and has been a participant again in 2020 [5]. While one of the first and most effective VR lifelog exploration systems, VRLE is a rather conservative VR adaptation of a conventional 2D user interface and even though different modes of user interaction were explored in [2], the query menu and horizontally scrolling result display are very similar to conventional UIs and do not take full advantage of the virtual space.

In strong contrast to VRLE, the lifelog exploration system described in [17] forgoes most conventional query modes and user interface elements, providing only a VR map to explore the lifelog data through their associated geospatial information. Although this results in an intuitive way to explore the spatial aspects of the lifelog data in a way not possible using conventional user interfaces, the restriction to one aspect of the data severely limits the system’s ability to take advantage of much of the information provided in lifelog search tasks, such as temporal and visual semantic information.

While the current research corpus on VR user interfaces for lifelog retrieval and multimedia retrieval in general is not conclusive, a systematic comparison of VRLE to a classical 2D system [3]

indicates that there is no clear advantage of using a 2D system, despite the mode of interaction being far more common. This shows that VR-based multimedia retrieval is a largely unexplored avenue for research. Therefore, in our work, we aim to combine the most effective, known methods from conventional retrieval interfaces with novel, purpose-built approaches that take advantage of virtual reality environments. First steps in that direction have already led to an experimental *Query-by-Sculpting* interface for retrieval in 3D model collections [1] and a VR based participation in the VBS [30].

3 SYSTEM OVERVIEW

vitivr is a general purpose, open-source¹ multimedia retrieval stack with support for images, audio, video, and 3D model collections [7], and both content-based similarity search as well as Boolean retrieval in metadata. The vitivr-VR user interface, described herein, can be seen as the latest addition to the stack and uses all the default programming interfaces offered by vitivr. Figure 1 illustrates the full stack of vitivr and vitivr-VR, with its three major components:

(i) *Cottontail DB* [6] is the database management system that stores all relevant information such as feature representations extracted from the multimedia data as well as any metadata. Furthermore, Cottontail DB facilitates execution of Boolean and nearest neighbor search (NNS) queries used in multimedia retrieval, (ii) *Cineast* [24, 25] is the retrieval engine at the core of the stack and handles query processing and feature transformation both during offline feature extraction from media collections as well as during online retrieval. Additionally, it takes care of query orchestration, score fusion and result set re-construction. An overview of its retrieval model can be found in [16], and (iii) *vitivr-VR* is the experimental, VR-based user interface presented in this paper, which offers all necessary functionality for query formulation and result exploration.

For the sake of completeness, the classical, web-based user interface, vitivr-ng, is also depicted in Figure 1. vitivr-VR sees itself as a prototypical extension to the stack in an attempt to investigate multimedia retrieval in virtual reality. As such, it complements vitivr-ng and does not aim to replace it. vitivr-VR is developed in Unity² with C# for the HTC Vive Pro and Valve Index, and communicates with Cineast using the RESTful API provided through its OpenAPI specifications.

vitivr-VR interfaces with VR hardware through the Unity OpenXR plugin³. We have chosen to target OpenXR as VR integration over more platform-specific options, such as the OpenVR plugin, even though this limits hardware functionality to the subset exposed through the OpenXR interface, for two reasons. Firstly, targeting OpenXR allows vitivr-VR to be developed mostly XR-backend agnostic, allowing it to be easily and quickly deployed to hardware not available during development or not supported by SteamVR. Secondly, the Unity OpenXR bindings are completely interaction system independent, which makes it easier to swap interaction systems or experiment with custom interactions. As interaction system for vitivr-VR, we use a mixture of the still in early development Unity XR Interaction Toolkit⁴ and our own custom interaction

¹see <https://www.vitrivr.org/>

²see <https://unity.com/>

³<https://docs.unity3d.com/Packages/com.unity.xr.openxr@latest>

⁴<https://docs.unity3d.com/Packages/com.unity.xr.interaction.toolkit@latest>




Figure 1: System overview for vitrivr-VR and its three major components: vitrivr-VR (UI), Cineast and Cottontail DB. For the sake of completeness, we also show the desktop user interface vitrivr-ng.

system for specific interactions such as the pinch gestures used to navigate the map for spatial query formulation.

The entire vitrivr stack is available as an open-source project on GitHub⁵ and participates in the 2021 installment of Google Summer of Code (GSoC), after previous participation in 2016 and 2018. vitrivr-VR itself cannot be downloaded yet but we plan on making it available as well in the near future.

3.1 Retrieval Modalities

vitrivr-VR makes use of three main retrieval modalities: concept-based, text-based, and spatio-temporal retrieval. These modalities are a subset of the ones also available to the web-based interface vitrivr-ng and were selected for their effectiveness in lifelog retrieval tasks based on our experiences from previous instances of the LSC.

Concept-based retrieval is enabled through Boolean search in Cottontail DB and performed on the concepts bundled with the LSC dataset, which are complemented by automatically extracted labels. Concepts may include prominent objects or the lifelogger’s current activity and are often subject of lifelog queries and therefore play an important role in lifelog retrieval.

Spatial (e.g., “I was in Oslo.”) and temporal information (e.g., “It was morning.”) also played a very important role in a lot of LSC tasks in recent years, which is why we included these modalities as well. Temporal retrieval is again powered by classical Boolean search, whereas spatial queries are realized through nearest neighbor search using spherical coordinates and the Haversine distance.

Full-text search is used mainly for searching the automatically generated image captions, as was used by vitrivr in previous iterations of the LSC. In addition, vitrivr-VR also leverages a text-based retrieval feature based on a visual-text co-embedding. Capable of

capturing a more detailed semantic representation than concept-tags, while being more flexible to different formulations than fixed scene captions, the effectiveness of visual-text co-embeddings was demonstrated in [19] and in an in-depth comparison of vitrivr and another system using similar embeddings [21].

Similarity search features, e.g., based on example images or color sketches, were not included in this iteration, since their use for the LSC is expected to be limited as a result of the textual nature of the task descriptions.

3.2 User Interaction in Virtual Reality

The user interaction in vitrivr-VR has been designed with interactivity and immersion at its core. Great care has been taken to tailor both the interactive retrieval process, which encompasses all interaction in vitrivr-VR from the initial query to query refinement and result exploration, as well as the interactions used to specify each aspect of a query for VR. In both of these areas, our aim was to adapt the most effective methods from systems designed for conventional interfaces to VR, and to combine them with new methods developed entirely with VR in mind.

3.2.1 Interactive Retrieval Process. The interactive retrieval process in vitrivr-VR is designed to allow iterative query refinement and query management. The most important components of this interactive retrieval process are the individual queries, the user-placeable result detail views and the query management.

The retrieval process starts with an initial query consisting of text-, concept- and spatio-temporal query terms. As the user browses the results and new information may have been added to the retrieval prompt, the user can alter the query and retrieve a new set of results. Not only does vitrivr-VR store the results of user issued queries, it also retains the user’s browsing position when a new query is issued to allow users to quickly return to exploring

⁵see <https://github.com/vitrivr>



Figure 2: An example of the interactive map for spatial query formulation centered on Basel, Switzerland. The globe mini-map on the left shows the location of the detail-map on the right.

previous result sets in case the refined query does not yield more promising results.

To make use of the virtual space during the interactive retrieval process, result detail views may be pulled out of a result set and placed anywhere in space. These pinned results also remain when switching between query results and thereby allow results to be compared and considered across queries before submission. The result detail views also expose further information about results of interest, such as associated concepts and metadata, which may be used to further refine the query.

3.2.2 Text-based Query Formulation. Text-based queries and also concept-based queries have proven to be very important in a lifelog search setting and both rely on textual input by the user. As primary text input method, vitrivr-VR uses speech-to-text, which allows fast, hands-free input of text in VR. Speech-to-text makes it easy to specify long text-based queries that are difficult and tedious to type without a physical keyboard. This makes speech-to-text especially well suited for full-text search on the automatically generated image captions and as input to the visual-text co-embedding. While individual keywords work well for concept-based search, the visual-text co-embedding is able to benefit from the additional semantic information contained in full sentences captured through speech-to-text.

In addition to speech-to-text, an optional contact-based virtual keyboard can be used to make small corrections and input hard-to-pronounce or non-English words. This contact-based keyboard is most useful for search of visible text extracted through OCR, as these often contain building and place names that may contain very unique spelling difficult to specify through speech-to-text.

3.2.3 Spatial Query Formulation. To make use of the spatial information contained in the lifelog data, vitrivr-VR allows the formulation of spatial queries through a map-based interface. The map-based query formulation interface consists of two parts as seen in

Figure 2: a flat, zoom- and scrollable detail-map and a globe mini-map. While the globe mini-map can be used to roughly pinpoint a location, the detail-map can be used to specify query locations with high precision by adjusting the map’s level of zoom to the required level of detail. The two maps are connected such that approximate locations of interest can be selected in the globe mini-map to be displayed and viewed on the detail-map, from which query locations can then be selected with high precision.

The interaction modes of the detail-map are inspired by existing touchscreen-based map interactions and those used with physical maps. Scroll interactions are performed by grabbing and dragging the map with either hand, while the level of zoom is adjusted by grabbing the map with both hands and moving them closer together to zoom out and farther away to zoom in, similar to the pinch gesture used in touch interfaces. Specifying query locations is done by placing virtual pins, such as the one seen in the top right of Figure 2, at the desired locations. To avoid the need to repeatedly change the map’s zoom level when scrolling large distances, the globe mini-map allows users to move the center of the detail-map quickly to a rough location anywhere on the globe. Interacting with the globe mini-map is analogous to interacting with a physical globe, allowing it to be grabbed, moved and rotated to be easily viewed from any angle.

The map data used by the spatial query formulation interface is loaded through a modified version of the Mapbox Unity Package⁶ and includes OpenStreetMap⁷ data.

3.2.4 Result Exploration. Query results are arranged cylindrically around the user as postcard-sized images, as seen in Figure 3. The view retains the grid structure intuitive to users of conventional interfaces, while making use of the additional freedoms of VR by surrounding the user. Results can be scrolled horizontally, revealing further results replacing those already viewed. While this method

⁶<https://www.mapbox.com/unity/>

⁷<https://www.openstreetmap.org>



Figure 3: Cylindrical results view as shown from a third-person perspective.

of result display is reminiscent of result displays in conventional interfaces [29] and does not make full use of virtual space by itself, this single-layered approach avoids result images occluding each other while allowing a large number of results to be browsed simply by looking around the virtual space.

Individual result items can be ‘popped’ out of the display and shown in a detailed view that also gives access to metadata and detected concepts. These result item detail views can be moved and positioned around the virtual space as reference or for later consideration. This allows individual results to be compared across queries, neighboring segments to be viewed and even the segment to be submitted to the competition system [23] for evaluation at any time in a competition setting.

In the lifelog setting, a piece of data is rarely independent and usually only appears in the context of a series of data. To contextualize query results within the data-series from which they originate, vitrivr-VR offers a sequence view for each result item, accessible from their detail view. An example of a sequence view is shown in Figure 4.

This sequence view shows the selected result item and a number of its sequence neighbors as slices inside a box in virtual space. Individual slices from this sequence can be inspected by hovering over them with a hand. By pulling the trigger on the selecting hand, the detailed view of the selected item can be accessed. The handle at the front of the view can be pulled toward the user like a drawer handle to elongate the sequence view and increase the spacing between the sequence items, making browsing easier. This sequence view is very space-efficient and allows a sequence of lifelog images to be browsed more quickly and intuitively than through conventional flat interfaces.

4 CONCLUSION

In this paper, we presented vitrivr-VR, a virtual reality multimedia retrieval system. vitrivr-VR features a VR interface designed to




Figure 4: Sequence view showing the neighbors of a query result. Moving a hand through the sequence displays the closest item to the hand above the sequence as shown.

combine the most effective methods from conventional user interfaces translated into the virtual space with interaction methods only possible in VR. We expect vitrivr-VR to be competitive in a lifelog search competition setting and to gain valuable insights into both the application of methods from conventional interfaces in VR as well as VR specific interaction methods.

While we take a big step in the direction of interactive multimedia retrieval designed for VR with vitrivr-VR, there is still a lot of untrod ground to investigate. In terms of both result display and exploration, there are still many aspects to be explored, such as display methods that make efficient use of virtual space and the balance between virtual space usage and visual overload. Furthermore, the influence of the virtual environment during tasks such as multimedia search and exploration has yet to be investigated.

ACKNOWLEDGMENTS

This work was partly supported by the Swiss National Science Foundation (project “Participatory Knowledge Practices in Analogue and Digital Image Archives”, contract no. CRSII5_193788) and the Hasler Foundation (project “City-Stories: Spatio-temporal Search over Crowdsourced Content”, contract no. 17055).

REFERENCES

- [1] Samuel Börlin, Ralph Gasser, Florian Spiess, and Heiko Schuldt. 2020. 3D Model Retrieval Using Constructive Solid Geometry in Virtual Reality. In *IEEE International Conference on Artificial Intelligence and Virtual Reality, AIVR 2020, Virtual Event, The Netherlands, December 14-18, 2020*. IEEE, 373–374. <https://doi.org/10.1109/AIVR50618.2020.00077>

- [2] Aaron Duane and Cathal Gurrin. 2019. User interaction for visual lifelog retrieval in a virtual environment. In *International Conference on Multimedia Modeling*. Springer, Springer International Publishing, Cham, 239–250.
- [3] Aaron Duane and Cathal Gurrin. 2020. Baseline analysis of a conventional and virtual reality lifelog retrieval system. In *International Conference on Multimedia Modeling*. Springer, 412–423.
- [4] Aaron Duane, Cathal Gurrin, and Wolfgang Huerst. 2018. Virtual reality lifelog explorer: lifelog search challenge at ACM ICMR 2018. In *Proceedings of the 2018 ACM Workshop on The Lifelog Search Challenge*. 20–23.
- [5] Aaron Duane, Björn Þór Jónsson, and Cathal Gurrin. 2020. VRLE: Lifelog Interaction Prototype in Virtual Reality: Lifelog Search Challenge at ACM ICMR 2020. In *Proceedings of the Third Annual Workshop on Lifelog Search Challenge*. 7–12.
- [6] Ralph Gasser, Luca Rossetto, Silvan Heller, and Heiko Schuldt. 2020. Cottontail DB: an open source base system for multimedia retrieval and analysis. In *Proceedings of the 28th ACM International Conference on Multimedia*.
- [7] Ralph Gasser, Luca Rossetto, and Heiko Schuldt. 2019. Multimodal Multimedia Retrieval with vitivr. In *Proceedings of the 2019 on International Conference on Multimedia Retrieval, ICMR 2019, Ottawa, ON, Canada, June 10-13, 2019*. ACM, 391–394. <https://doi.org/10.1145/3323873.3326921>
- [8] Ralph Gasser, Luca Rossetto, and Heiko Schuldt. 2019. Towards an all-purpose content-based multimedia information retrieval system. *arXiv preprint arXiv:1902.03878* (2019).
- [9] Cathal Gurrin, Tu-Khiem Le, Van-Tu Ninh, Duc-Tien Dang-Nguyen, Björn Þór Jónsson, Jakub Lokoč, Wolfgang Hürst, Minh-Triet Tran, and Klaus Schoeffmann. 2020. Introduction to the Third Annual Lifelog Search Challenge (LSC’20). In *Proceedings of the 2020 International Conference on Multimedia Retrieval*. 584–585.
- [10] Cathal Gurrin, Alan F Smeaton, and Aiden R Doherty. 2014. Lifelogging: Personal big data. *Foundations and trends in information retrieval* 8, 1 (2014), 1–125.
- [11] Cathal Gurrin, Björn Þór Jónsson, Klaus Schöffmann, Duc-Tien Dang-Nguyen, Jakub Lokoč, Minh-Triet Tran, Wolfgang Hürst, Luca Rossetto, and Graham Healy. 2021. Introduction to the Fourth Annual Lifelog Search Challenge, LSC’21. In *Proc. International Conference on Multimedia Retrieval (ICMR’21)*. ACM, Taipei, Taiwan.
- [12] Silvan Heller, Mahnaz Amiri Parian, Ralph Gasser, Loris Sauter, and Heiko Schuldt. 2020. Interactive lifelog retrieval with vitivr. In *Proceedings of the Third Annual Workshop on Lifelog Search Challenge*.
- [13] Silvan Heller, Ralph Gasser, Cristina Illi, Maurizio Pasquinelli, Loris Sauter, Florian Spiess, and Heiko Schuldt. 2021. Towards explainable interactive multi-modal video retrieval with vitivr. In *International Conference on Multimedia Modeling*.
- [14] Silvan Heller, Ralph Gasser, Mahnaz Parian, Sanja Popovic, Luca Rossetto, Loris Sauter, Florian Spiess, and Heiko Schuldt. 2021. Interactive Multimodal Lifelog Retrieval with vitivr at LSC 2021. In *Proceedings of the Fourth Annual Workshop on Lifelog Search Challenge*.
- [15] Silvan Heller, Mahnaz Parian, Maurizio Pasquinelli, and Heiko Schuldt. 2020. Vitivr-Explore: Guided Multimedia Collection Exploration for Ad-hoc Video Search. In *International Conference on Similarity Search and Applications*.
- [16] Silvan Heller, Loris Sauter, Heiko Schuldt, and Luca Rossetto. 2020. Multi-Stage Queries and Temporal Scoring in Vitivr. In *2020 IEEE International Conference on Multimedia & Expo Workshops (ICMEW)*.
- [17] Wolfgang Hürst, Kevin Ouwehand, Marijn Mengerink, Aaron Duane, and Cathal Gurrin. 2018. Geospatial access to lifelogging photos in virtual reality. In *Proceedings of the 2018 ACM Workshop on The Lifelog Search Challenge*. 33–37.
- [18] Jakub Lokoč, Gregor Kovalčík, Bernd Münzer, Klaus Schöffmann, Werner Bailer, Ralph Gasser, Stefanos Vrochidis, Phuong Anh Nguyen, Sitapa Rujikietgumjorn, and Kai Uwe Barthel. 2019. Interactive search or sequential browsing? A detailed analysis of the video browser showdown 2018. *ACM Transactions on Multimedia Computing, Communications, and Applications (TOMM)* 15, 1 (2019), 1–18.
- [19] Jakub Lokoč, Tomáš Souček, Patrik Veselý, František Mejzlík, Jiaqi Ji, Chaoyi Xu, and Xirong Li. 2020. A W2VV++ case study with automated and interactive text-to-video retrieval. In *Proceedings of the 28th ACM International Conference on Multimedia*. 2553–2561.
- [20] Luca Rossetto, Ralph Gasser, Silvan Heller, Mahnaz Amiri Parian, and Heiko Schuldt. 2019. Retrieval of structured and unstructured with vitivr. In *Proceedings of the Second Annual Workshop on Lifelog Search Challenge*.
- [21] Luca Rossetto, Ralph Gasser, Silvan Heller, Mahnaz Parian-Scherb, Loris Sauter, Florian Spiess, Heiko Schuldt, Ladislav Peska, Tomas Soucek, Miroslav Kratochvil, et al. 2021. On the User-centric Comparative Remote Evaluation of Interactive Video Search Systems. *IEEE MultiMedia* (2021).
- [22] Luca Rossetto, Ralph Gasser, Jakub Lokoc, Werner Bailer, Klaus Schoeffmann, Bernd Muenzer, Tomas Soucek, Phuong Anh Nguyen, Paolo Bolettieri, Andreas Leibeseder, et al. 2020. Interactive video retrieval in the age of deep learning-detailed evaluation of vbs 2019. *IEEE Transactions on Multimedia* (2020).
- [23] Luca Rossetto, Ralph Gasser, Loris Sauter, Abraham Bernstein, and Heiko Schuldt. 2021. A system for interactive multimedia retrieval evaluations. In *International Conference on Multimedia Modeling*. Springer, 385–390.
- [24] Luca Rossetto, Ivan Giangreco, Silvan Heller, Claudiu Tănase, and Heiko Schuldt. 2016. Searching in video collections using sketches and sample images—the Cineast system. In *International Conference on Multimedia Modeling*.
- [25] Luca Rossetto, Ivan Giangreco, and Heiko Schuldt. 2014. Cineast: a multi-feature sketch-based video retrieval engine. In *2014 IEEE International Symposium on Multimedia*.
- [26] Luca Rossetto, Ivan Giangreco, Claudiu Tanase, and Heiko Schuldt. 2016. vitivr: A flexible retrieval stack supporting multiple query modes for searching in multimedia collections. In *Proceedings of the 24th ACM international conference on Multimedia*.
- [27] Luca Rossetto, Mahnaz Amiri Parian, Ralph Gasser, Ivan Giangreco, Silvan Heller, and Heiko Schuldt. 2019. Deep learning-based concept detection in vitivr. In *International Conference on Multimedia Modeling*.
- [28] Loris Sauter, Mahnaz Amiri Parian, Ralph Gasser, Silvan Heller, Luca Rossetto, and Heiko Schuldt. 2020. Combining boolean and multimedia retrieval in vitivr for large-scale video search. In *International Conference on Multimedia Modeling*.
- [29] Klaus Schoeffmann, David Ahlström, and Laszlo Böszörményi. 2012. Video browsing with a 3D thumbnail ring arranged by color similarity. In *International Conference on Multimedia Modeling*. Springer, 660–661.
- [30] Florian Spiess, Ralph Gasser, Silvan Heller, Luca Rossetto, Loris Sauter, and Heiko Schuldt. 2021. Competitive interactive video retrieval in virtual reality with vitivr-VR. In *International Conference on Multimedia Modeling*.